

US009638418B2

(12) United States Patent Chiu et al.

(54) OXYGEN FIRED STEAM GENERATOR

(75) Inventors: **John H. Chiu**, West Hartford, CT (US); **George D. Mylchreest**, Simsbury, CT

(US)

(73) Assignee: General Electric Technology GmbH,

Baden (CH)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 1590 days.

(21) Appl. No.: 12/468,290

(22) Filed: May 19, 2009

(65) Prior Publication Data

US 2010/0294180 A1 Nov. 25, 2010

(51) Int. Cl. F23L 7/00 (2006.01) F23C 10/10 (2006.01)

(52) **U.S. CI.** CPC *F23L 7/007* (2013.01); *F23C 10/10* (2013.01); *F23C 2206/103* (2013.01); *Y02E*

20/344 (2013.01)

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

4,084,545 A *	4/1978	Nack et al	110/245
4,193,773 A *	3/1980	Staudinger 11	10/101 R
4,823,712 A *	4/1989	Wormer	110/245
4,969,930 A *	11/1990	Arpalahti	110/347

(10) Patent No.: US 9,638,418 B2 (45) Date of Patent: May 2, 2017

5,344,629	A *	9/1994	Engstrom 4	23/239.1
6,505,567	B1 *	1/2003	Anderson et al	110/243
7,331,313	B2 *	2/2008	Weissinger et al	122/4 D
8.196.532	B2 *	6/2012	Andrus et al	110/245

2004/0261671 A1* 12/2004 Taylor 110/261 FOREIGN PATENT DOCUMENTS

DE 19703197 8/1998

OTHER PUBLICATIONS

PCT International Search Report and The Written Opinion of the International Searching Authority dated Jul. 27, 2010—(PCT/US2010/034439).

* cited by examiner

Primary Examiner — David J Laux (74) Attorney, Agent, or Firm — GE Global Patent Operation; Cynthia W. Flanigan

(57) ABSTRACT

In a method for operating a steam generator, a transport reactor is provided. Only a substantially pure oxygen feed stream is introduced into the transport reactor in an amount sufficient to maintain the transport reactor at or above a specific system load. The specific load is the system load when only the substantially pure oxygen feed stream is provided to the transport reactor at a minimum flow velocity for operating the transport reactor. A fuel is combusted in the presence of the substantially pure oxygen feed stream to produce a flue gas, which contains solid material. The solid material is separated from the flue gas and passed to a heat exchanger. The heat exchange may be one of a moving bed heat exchanger or a fluidized bed heat exchanger. The solid material is directed to the transport reactor to contribute to the combustion process.

20 Claims, 2 Drawing Sheets

